

Full 4K HDMI 2.0 compatible optical receiver

Ref. EXT-HDMI20-OPT-RX



HDMI 2.0 over optical fiber receiver for long range signal management



4K60
4:4:4

HFR
up to
144Hz

HDMI
2.0

HDCP
2.2

HDR

FIBER
OPTICAL

Overview

The Analog Way **EXT-HDMI20-OPT-RX** is an HDMI 2.0 over fiber receiver designed to transfer uncompressed HDMI 2.0 class 4K signal with embedded audio to up to 600m (~2000 ft.) or a full HD signal to up to 2500m (~8200 ft.) over one multimode fiber cable. It supports resolutions up to 4K60 8 bits 4:4:4 or 4K60 10 bits 4:2:2 as well as custom formats such as 8192x1080@60Hz. It also handles up to 8 embedded audio channels and features advanced HDCP 1.4 and 2.2 handshake as well as HDR compatibility. Its solid aluminum housing provides a mechanical protection as well as excellent heat dissipation.

Key features

- ▶ Single fiber input port (standard SC connector)
- ▶ Output port fully compatible with HDMI 2.0
- ▶ Uncompressed video up to 18 Gbps bandwidth
- ▶ True 4K60 4:4:4 performance
- ▶ Status LED for easy troubleshooting
- ▶ HDR compliant with HDR10 and HLG
- ▶ Supports up to 8 embedded audio channels per output (PCM)
- ▶ EDID management
- ▶ Compliant with HDCP 1.4 and HDCP 2.2
- ▶ Ruggedized design

Enclosure dimensions

- ▶ W 4.35" x H 0.45" x D 1.40"
- ▶ W 110.5 mm x H 11.4 mm x D 35.5 mm

Length of pigtail HDMI cable

- ▶ 31.5" / 800mm

Length of pigtail USB cable

- ▶ 39.4" / 1000mm

Weight

- ▶ 145g / 0.32 lbs

Operating conditions

- ▶ Temperature: 0 to 50°C (32 to 122°F)
- ▶ Humidity: 10% to 90%, non-condensing

Power consumption

- ▶ 0.8W (1080p60) / 1W (4K/60)

Warranty

- ▶ 3-year warranty on parts and labor back to factory
- ▶ Broken connectors are not covered by warranty

Safety Compliance (general)

- ▶ Compliance: CE
- ▶ EMC compliance: IEC/EN 55032:2015 and IEC/EN 55035:2017
- ▶ Safety: IEC/EN 62368-1:2014

Safety Compliance (laser)

- ▶ IEC/EN 60825-1:2014-05 Ed. 3.021CFR Subchapter J Parts 1040.40 and 1040.11
- ▶ Laser class: Class 1

Technical Specifications

Standard SC connector

Multimode fiber

Laser class 1

Up to 18 Gbps bandwidth

8-bit formats up to:

- UHD/4K@60Hz 4:4:4 (no chroma subsampling)
- 2560x1440@144Hz 4:4:4

10-bit formats up to:

- 4K60 with 4:2:2 chroma subsampling
- 4K30 4:4:4
- 2560x1440@60Hz 4:4:4

Extra-wide custom formats such as 8192x1080@60Hz (8k x 1k) or 1080x8192@60Hz

Up to 2500m (~8200 ft.) in full HD

Up to 600m (~2000 ft.) in 4K

Compliant with HDCP 1.4 and HDCP 2.2

Supports BT.709 and BT.2020 color spaces

No additional latency

Compatible with Analog Way's LivePremier HDMI 2.0 over fiber output card (ref. ACC-AQL-OUT-HDMI-FBR) and HDMI 2.0 over fiber transmitter (ref. EXT-HDMI20-OPT-TX)

External power adaptor / USB (A-type connector)

Aluminum machined housing

Rack mountable inside Analog Way's power trays (ref. OPT-POWERTRAY-SC, OPT-POWERTRAY-NTD and OPT-POWERTRAY-NTQ)

Specifications subject to change without prior notice

EXT-HDMI20-OPT-RX-EN-12/01/2020